

Groove

FilaSorb™ 24



Product Detail

Product Groove

Surface Ceiling

Composition 100% Polyester

MaterialFilaSorb™Recycled Content60% min.

Thickness 24mm | 0.94" +/- 10% Weight 0.98 lb/ft² +/- 10%

Length 110"

Depth 8" or 10" or 12"

Custom size available upon request.

Technical Data

Fire Test Method Number

Indoor Air Quality

Light Fastness

AS ISO 9705:Group 1

ASTM E84-17a Class A

Low VOCs emission, formaldehyde

and Phenol-free


ISO 105-B02 1994, 6-7

Acoustic Performance

Sound Absorption

ISO 354-2006

NRC 0.60



Frequency f(Hz)	125	250	500	1000	2000	4000	NRC
24mm as	0.02	0.57	0.41	0.58	0.87	0.85	0.60

Guarantees

Lead Time

Light Fastness Warranty

Customizable

Ships in 4-6 weeks

10 Years*

Yes

* conditions apply

Environmental Attributes

- Declare Certification
- LCB Red List Free
- Phenol And Formaldehyde Free
- Low VOC
- CDPH Compliance
- Aligns With Building Standards













Groove 1 (GR1)

Elevation




Perspective




Groove 2 (GR2)

Elevation



Perspective




* Number of connections may vary depending on length




Recommended Layouts


Layout 1 (100% GR1)



Layout 2 (100% GR2)




Layout 3 (50% GR1 & 50% GR2)




Mounting Methods


Cable




Cable To Deck




Cable To T Grid




Cable To Unistrut




Swivel Cable To Deck




Threaded Rod




Threaded Rod To Unistrut



Twist Lock To T Grid



Magnet To T Grid





Colorways



